

ALGEMEEN

Serie	Uf(min) < Uf(Gemiddelde) < Uf(max) W/m2K	Warmtedoorgangscoefficient glas (Ug) W/m2K										
		1.5	1.4	1.3	1.2	1.1	1.0	0.9	0.8	0.7	0.6	0.5
STAR 90 i+	0.78 < 1.09 < 1.98	1.5	1.4	1.3	1.2	1.2	1.1	1.0	0.9	0.8	0.8	0.7
STAR 90 i	0.85 < 1.20 < 1.84	1.5	1.4	1.3	1.3	1.2	1.1	1.0	0.9	0.9	0.8	0.7
STAR 75 i+	1.09 < 1.43 < 2.09	1.5	1.5	1.4	1.3	1.2	1.1	1.1	1.0	0.9	0.8	0.7
STAR 90	1.54 < 1.77 < 2.32	1.6	1.5	1.5	1.4	1.3	1.2	1.1	1.1	1.0	0.9	0.8
STAR 75 i	1.47 < 1.82 < 2.42	1.6	1.5	1.5	1.4	1.3	1.2	1.1	1.1	1.0	0.9	0.8
ECOFUTURAL i+	1.41 < 1.88 < 2.11	1.6	1.6	1.5	1.4	1.3	1.2	1.2	1.1	1.0	0.9	0.8
STAR 75	1.92 < 2.01 < 2.51	1.7	1.6	1.5	1.4	1.3	1.3	1.2	1.1	1.0	0.9	0.9
NEW PANORAMA i	1.53 < 2.01 < 2.41	1.7	1.6	1.5	1.4	1.3	1.3	1.2	1.1	1.0	0.9	0.9
STAR 75 OC	1.73 < 2.14 < 2.60	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.1	1.0	1.0	0.9
ECOFUTURAL i	1.76 < 2.15 < 2.35	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.1	1.0	1.0	0.9
ULTRAGLIDE i+	1.21 < 2.15 < 2.47	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.1	1.0	1.0	0.9
ECOFUTURAL	2.08 < 2.54 < 2.88	1.8	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.1	1.0	1.0
INDUS	2.30 < 2.59 < 2.75	1.8	1.7	1.6	1.5	1.5	1.4	1.3	1.2	1.1	1.1	1.0
NEW PANORAMA	2.25 < 2.67 < 3.00	1.8	1.7	1.6	1.6	1.5	1.4	1.3	1.2	1.2	1.1	1.0
ULTRAGLIDE i	1.57 < 2.72 < 3.61	1.8	1.7	1.6	1.6	1.5	1.4	1.3	1.2	1.2	1.1	1.0
FUTURAL	2.15 < 2.73 < 3.48	1.8	1.7	1.6	1.6	1.5	1.4	1.3	1.2	1.2	1.1	1.0
LUXUS	2.39 < 2.77 < 3.00	1.8	1.7	1.7	1.6	1.5	1.4	1.3	1.3	1.2	1.1	1.0
STEELLOOK 1000	2.56 < 2.80 < 3.19	1.8	1.7	1.7	1.6	1.5	1.4	1.3	1.3	1.2	1.1	1.0
ULTRAGLIDE	2.28 < 2.95 < 3.73	1.8	1.8	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.1	1.0
VISOLINE	2.56 < 2.99 < 4.14	1.9	1.8	1.7	1.6	1.5	1.5	1.4	1.3	1.2	1.1	1.1
VISOGLIDE 500N i	1.93 < 3.21 < 5.26	1.9	1.8	1.7	1.7	1.6	1.5	1.4	1.3	1.3	1.2	1.1
GREENSLIDE	2.30 < 3.54 < 5.95	2.0	1.9	1.8	1.7	1.6	1.6	1.5	1.4	1.3	1.2	1.2
VISOGLIDE 500N	2.06 < 3.59 < 5.45	2.0	1.9	1.8	1.7	1.7	1.6	1.5	1.4	1.3	1.3	1.2
SUPERGLIDE	3.12 < 4.41 < 6.17	2.1	2.1	2.0	1.9	1.8	1.7	1.7	1.6	1.5	1.4	1.3
SLIDE	2.88 < 4.74 < 6.03	2.2	2.1	2.0	2.0	1.9	1.8	1.7	1.6	1.6	1.5	1.4

Lineaire thermische transmissie coëfficiënt = 0.036 W/mK
Aluminium oppervlakte = 20 % & Glas oppervlakte = 80 %

Voor de holtes tussen de isolatie stegen is een emissiviteits coëfficiënt van 0.3 gebruikt (geoxideerd aluminium)
Formules volgens de internationale normen ISO 10077-1 & 10077-2